Mipa Kunststoffreiniger

Technical data sheet

Intended use

Mipa Kunststoffreiniger is a CFC-free cleaning agent for all common plastics. It eliminates electrostatic charges and prevents their regeneration. Electrostatic charge causes higher dust attraction during the coating of plastic parts. This product can be applied by paintbrush, brush, wipe, sponge and by spray gun.


Spreading rate: --

Processing instructions



Colour

colourless



Mixing ratio

Hardener	by weight (lacquer : hardener)	by volume (lacquer : hardener)
--	--	--



Hardener

for complete paintwork	for partial paintwork
--	--




Pot life

--



Thinner

--




Spray viscosity

gravity spray gun	Airmix/Airless
--	--



Application mode

Application mode	Hardener	pressure (bar)	nozzle (mm)	spray passes	Thinner
--	--	--	--	--	--



Flash-off time

--

Dry coat thickness

--



Drying time

object temperature	dust dry	set to touch	ready for assembly	sandable	recoatable
--	--	--	--	--	--

This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.

MIPA SE · Am Oberen Moos 1 · D-84051 Essenbach · Tel.: +49(0)8703/922-0 · Fax: +49(0)8703/922-100 · mipa@mipa-paints.com · www.mipa-paints.com

Note

Storage:	at least 3 years in unopened original containers.
VOC Regulation :	EU limit value for this product (category B/a): 850 g/l This product contains max. 747 g/l of VOC.
Processing conditions:	from +10° C and up to 80 % relative air humidity. Ensure an adequate air ventilation.
Processing instructions:	Please see technical data sheet L7 „coating plastics". The temperature in the booth and of the material should be between 18 - 24 °C. Use always two different, clean clothes: one for applying the product and one for rubbing dry.

This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.

MIPA SE · Am Oberen Moos 1 · D-84051 Essenbach · Tel.: +49(0)8703/922-0 · Fax: +49(0)8703/922-100 · mipa@mipa-paints.com · www.mipa-paints.com